

NEW PS2.6 - HI-RES SLIM INDOOR SCREEN IN STOCK

Modular Design

- Curved cabinet and straight cabinet
- Die Cast Aluminum Cabinet
- Corner Protection
- Double gasket fast Locks for better flatness
- All in one power box
- Fully modular structure design:
box frame + module +control box



Fast Maintenance

- Module with safety lock + magnetic design, supports front and rear maintenance
- Single cabinet only 7.3KG, which is 10% lighter than the general rental products with the same size

Fast & Rear Module Maintenance

Supports front & rear maintenance
easy to replace module

Quick Swappable Power Box

Replace in seconds with a quick release
system



Parameter

Value

Pixel Configuration

SMD1515

Pixel Pitch(mm)

2.6

Pixel matrix per panel

192x192

Pixel density (pixels/sqm)

147456

Cabinet Dimensions (WxHxD)/mm

500x500x66

Module Dimensions (WxD)/mm

250x250

Panel material

Die Castng Aluminum

Cabinet weight (kg/panel)

7.3

Color Grayscale (Bit)

14

Gray Scale per Color (level)

16384

Refresh Rate (Hz)

3840

Driving Type

1/24

Brightness (nits)

800-1000

Optimal Horizontal Viewing Angle

170

Optimal Vertical Viewing Angle

+/- 80

Contrast ratio

9100:1

AC Input Voltage (v)

Ac: 100V~240V

AC Input Power Maximum Value (W/m²)

415

AC Input Power Typical Value (W/m²)

139

Storage Temperature (° C)

-40-60

Working Temperature (° C)

0-40

IP rating (Front/Rear)

IP40/IP20

Working Humidity (RH)

10%~60% non-condensing

Lifetime Typical Value (hrs)

100000

Cabinet Installation

Rental

Certifications

CE, CB, EMC, FCC TUV

